

SparcoZone²™ Multiple Zoning Control for Hydronic Heating Systems

Save time, parts, labor and money. Up to 4 hours on typical installation.



Pre-assembled, pre-wired and ready to connect. The multiple zone valve concept utilizing Honeywell's "Intelligence" with the R8889 Zone Valve Control Panel and pre-assembled return manifold is fitted with the MZV series *PowerTrack* Zone Valves for multiple zone control.



Pre-assembled manifold with *PowerTrack*™ Zone Valves minus control panel



Snow melt return manifold



Supply header

SparcoZone2™ hydronic zoning control system is an electronically operated 3 or 4 multiple zone valve controller. Pre-assembled supply manifold fitted with fast-acting Honeywell *PowerTrack*™ zone valves and Honeywell R8889 Zone Valve Panel. To help save valuable installation time and parts the unit is pre-wired for easy set-up and is ready to install.



Features/Benefits

- Saves time, labor, parts and money
- Professional installation appeal
- Honeywell proven performance
- Priority switch for Domestic Hot Water
- Clearly marked wiring panel terminals for easy installation
- LED lights for easy diagnostics of individual zone control and burner operation
- Field replaceable relays and transformers
- Fast-acting *PowerTrack*™ zone valves
- Built-in pre-balancing plug for individual zone flow control
- Sweat or Threaded connection bronze manifold
- Easily expanded up to 16 Zones
- UL Listed



PRODUCT NO.	DESCRIPTION		SIZE	
	ZONES	CONTROLS	MAIN	BRANCH
SZ3S1	3	WITHOUT CONTROLS	1 1/4" NPT/SWEAT	3/4" SWEAT
SZ4S1	4		1 1/4" NPT/SWEAT	3/4" SWEAT
SZ3T1	3		1 1/4" NPT/SWEAT	3/4" THREADED
SZ4T1	4		1 1/4" NPT/SWEAT	3/4" THREADED
S2Z3S3	3	INCLUDES CONTROLS	1 1/4" NPT/SWEAT	3/4" SWEAT
S2Z4S3	4		1 1/4" NPT/SWEAT	3/4" SWEAT
S2Z3T3	3		1 1/4" NPT/SWEAT	3/4" THREADED
S2Z4T3	4		1 1/4" NPT/SWEAT	3/4" THREADED
SH4S	4 ZONE SUPPLY HEADER ONLY		1 1/4" NPT/SWEAT	3/4" SWEAT
SH4T	4 ZONE SUPPLY HEADER ONLY		1 1/4" NPT/SWEAT	3/4" THREADED
SZ8889-RP	HYDRONIC ZONE VALVE CONTROL ONLY			
MZV520-RP	POWERTRACK™ OPERATOR		WHEN ORDERED SEPARATELY	
SZ001	VALVE KIT			
SZ002	PLUG KIT			
SZ4S1L	SNOW MELT RETURN MANIFOLD		SEE SD/IS 590 FOR INFORMATION	

Maximum Temperature - 220°F. Maximum Pressure - 125psi

Honeywell-Water Controls

65 Access Road, Warwick, Rhode Island 02886 USA

Phone: (401) 738-4290 Fax: (401) 738-4156

Toll Free Fax: (800) 777-2726 www.honeywellwatercontrols.com

© 2003 Honeywell, Inc.